

UNCLASSIFIED

AD NUMBER
AD401579
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Foreign Government Information; 17 FEB 1961. Other requests shall be referred to US Library of Congress, Attn: Aerospace Technology Division, Washington, DC.
AUTHORITY
ATD ltr, 2 Dec 1965

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD


401 579

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

401 579

(5) 17511

21

Z/503/62/000/008/002/003
1011/1211

ASTIA FILE COPY

STEP

AUTHORS: (8) Linek, Allan and Novak, Tstirad

TITLE: (6) A special printing device with a transformation of
binary numbers into decimals expressed by the
international teletype codeSOURCE: (15) Československá akademie věd. Ústav matematických
strojů. Stroje na zpracování informací, no. 8, 1962,
121-134 (In Russian. Resumes in Czech and German)TEXT: The results of computations concerning crystal
structures, especially projections of electron densities, are
usually plotted by hand in the form of maps. A special computer
M-1 is used for computations at the crystal structures laboratory

Card 1/4

Z/503/62/000/008/002/003
1011/1211

A special printing....

of the Institute of technical physics of the Czechoslovak Academy of sciences. A teletype serves as an additional unit that prints the results on a sticky tape. Sticking this tape to a sheet of paper yields maps of wanted dimensions and forms. Up to now the results were printed in the octal system. We proposed a new device for printing the results in the decimal system. The device is designed for special crystallographic computations, but some of its parts or principles of operation can be used in other fields. In view of the speed of the M-1 output it is necessary to print a number of 6 characters (at the most) in a 1.5 seconds interval. We chose the relay as the building block of our device since we had previous experience in operating relay machines and because

Card 2/4

Z/503/62/000/008/002/003
I011/I211

A special printing...

of its simplicity and availability. We used the tape teletype because of the possibility of simultaneous perforation. The RFT51 teletype was modified by adding to it a camshaft pulse generator that derives its motion from the shaft. We aimed at building an independent printing unit capable of operating with all the computers in the laboratory. The block diagram of the binary to decimal and to teletype code transformer is given and its principle of operation is explained. The transformation is based on comparing the binary number to $m_1 \times 10^n$ ($m_1 = 8;4;2;1$) and then printing out the result, deducting the $10^n \sum m_i$ from the binary number and comparing the remainder to $m_1 \times 10^{n-1}$, and so on. A block diagram of the entire device is given and its operation is explained. Wiring diagrams of the one-tact decoder, the comparison circuit and the decoder that transforms the binary-

Card 3/4

Z/503/62/000/008/002/003
I011/I211

A special printing....

decimal number into a teletype code are given. The device does not print zeros unless there is a non-zero entry in a higher-order decimal place. The mechanical and electrical modifications of the RFT teletype were carried out and its operation was satisfactory. It should be added that the length of a tact is 75 msec. This operating speed can be dealt with by an Aritma relay. There are 8 figures and 2 tables.

ASSOCIATION: Institut technicheskey fiziki Chekhoslovatskoy
AN, (Institute of Technical Physics, Czechoslovak
AS) Prague

SUBMITTED: February 17, 1961

4/4